

## PRODUCT SPECIFICATIONS



### Main Unit

#### Type

Colour Laser Multifunctional

#### Core Functions

Standard: Print, Copy, Scan, Send, Store  
Optional: Fax

#### Processor

Canon Dual Custom Processor (Shared)

#### Control Panel

10.1" TFT LCD WSVGA Colour Flat-panel

#### Memory

4.0 GB RAM

#### Hard Disk Drive

Standard: 250 GB  
Maximum: 1 TB

#### Mirroring Hard Disk Drive

Optional: 250 GB, 1 TB  
Method: Raid1

#### Interface Connection

Network  
Standard: 1000Base-T/100Base-TX/10Base-T,  
Wireless LAN (IEEE 802.11 b/g/n)  
Optional: NFC, Bluetooth Low Energy

#### Others

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),  
USB 2.0 x1 (Device)

Optional: Serial Interface, Copy Control Interface

#### Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets  
Maximum: 6,350 Sheets

#### Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 550-sheet Paper Cassettes, 100-sheet  
Stack Bypass

Optional: Dual 550-sheet Paper Cassettes  
(CASSETTE FEEDING UNIT-AM1),  
2,450-sheet High-Capacity Paper Cassette  
(HIGH CAPACITY CASSETTE FEEDING  
UNIT-A1), 2,700-sheet Paper Deck  
(PAPER DECK UNIT-F1)

#### Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets  
Maximum: 3,450 Sheets  
(with External Finisher and Copy Tray)

#### Finishing Capabilities

Standard: Collate, Group  
With Inner  
Finisher: Collate, Group, Offset, Staple, Hole Punch,  
Staple-Free Staple, Staple On Demand

With External  
Finishers: Collate, Group, Offset, Staple, Booklet, Hole  
Punch, Staple-Free Staple, Staple On Demand

#### Supported Media Types

Paper  
Cassette 1: Thin, Plain, Recycled, Colour, Heavy,  
Pre-punched, Letterhead, Bond,  
Transparency, Envelope

Paper  
Cassette 2: Thin, Plain, Recycled, Colour, Heavy,  
Pre-punched, Letterhead, Bond,  
Transparency, Tab, Envelope

Stack Bypass: Thin, Plain, Recycled, Colour, Heavy,  
Pre-punched, Labels, Letterhead,  
Bond, Coated, Transparency, Tab,  
Tracing,<sup>1</sup> Envelope

#### Supported Media Sizes

Paper  
Cassette 1: Letter, Executive, Statement-R, Envelope  
[No.10 (COM10), DL, ISO-C5], Custom Size  
(3-7/8" x 5-7/8" to 11-3/4" x 8-1/2")

Paper  
Cassette 2: 12" x 18", 11" x 17", Legal, Letter, Letter-R,  
Executive, Statement-R, Envelope [No.10  
(COM10), Monarch, DL, ISO-C5], Custom Size  
(3-7/8" x 7-1/8" to 12" x 18")

Stack Bypass: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size (3-7/8" x 3-7/8" to 12-5/8" x 18"), Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18"), Free Size (3-7/8" x 5-1/2" to 12-5/8" x 18")

#### Supported Media Weights

Cassettes: 14 lb. Bond to 140 lb. Index (52 to 256 g/m<sup>2</sup>)  
Stack Bypass: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m<sup>2</sup>)  
Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m<sup>2</sup>)

#### Warm-up Time

From Power On: Approx. 10 Seconds<sup>2</sup>  
From Sleep Mode: Approx. 10 Seconds<sup>3</sup>  
Quick Startup Mode: Approx. 4 Seconds<sup>4</sup>

#### Dimensions (W x D x H)

24-3/8" x 29-1/4" x 37-3/8" (620 mm x 742 mm x 950 mm)<sup>5</sup>

#### Installation Space (W x D)

Basic: Stack Bypass + Cassette Drawers open: 37-1/8" x 46-3/8" (943 mm x 1,176 mm)

#### Weight

310.9 lb. (141 kg)<sup>6</sup>

## Print Specifications

#### Print Speed (BW and Colour)

C5560i III: Up to 60 ppm (Letter); Up to 36 ppm (Letter-R); Up to 34 ppm (Legal); Up to 32 ppm (11" x 17")  
C5550i III: Up to 50 ppm (Letter); Up to 30 ppm (Letter-R); Up to 29 ppm (Legal); Up to 27 ppm (11" x 17")  
C5540i III: Up to 40 ppm (Letter); Up to 24 ppm (Letter-R); Up to 23 ppm (Legal); Up to 22 ppm (11" x 17")  
C5535i III: Up to 35 ppm (Letter); Up to 23 ppm (Letter-R); Up to 21 ppm (Legal); Up to 18 ppm (11" x 17")

#### Print Resolution (dpi)

1200 x 1200, 600 x 600

#### Standard Page Description Languages

UFR II, PCL<sup>®</sup> 6, Adobe<sup>®</sup> PS<sup>®</sup> 3

#### Direct Print

Available from USB, Advanced Box, Remote UI, and Web Access<sup>7</sup>

#### Supported File Types

PDF, TIFF, JPEG, EPS,<sup>8</sup> XPS

#### Printing from Mobile Devices and Cloud-based Services

A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.

#### Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese),<sup>9</sup> Barcode Fonts<sup>10</sup>  
PS fonts: 136 Roman

#### Operating System<sup>11</sup>

UFR II: Windows<sup>®</sup> Server 2008/Windows<sup>®</sup> 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016, MAC OS X (10.9 or later)  
PCL: Windows Server 2008/Windows 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016  
PS: Windows Server 2008/Windows 7/Server 2008 R2/Server 2012/Windows 8.1/Server 2012 R2/Windows 10/Server 2016, MAC OS X (10.9 or later)  
PPD: MAC OS X (10.3.9 or later), Windows 7/8.1/10

#### Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Forced Hold Printing, Watermark, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Front/Back Covers, Toner Reduction, Poster Printing

## Copy Specifications

#### Copy Speed (BW and Colour)

C5560i III: Up to 60 ppm (Letter); Up to 36 ppm (Letter-R); Up to 34 ppm (Legal); Up to 32 ppm (11" x 17")  
C5550i III: Up to 50 ppm (Letter); Up to 30 ppm (Letter-R); Up to 29 ppm (Legal); Up to 27 ppm (11" x 17")  
C5540i III: Up to 40 ppm (Letter); Up to 24 ppm (Letter-R); Up to 23 ppm (Legal); Up to 22 ppm (11" x 17")  
C5535i III: Up to 35 ppm (Letter); Up to 23 ppm (Letter-R); Up to 21 ppm (Legal); Up to 18 ppm (11" x 17")

#### First-Copy-Out Time (Letter)

C5560i III: As fast as 2.9 seconds (BW)/4.5 seconds (Colour)  
C5550i III: As fast as 3.5 seconds (BW)/5.2 seconds (Colour)  
C5540i III: As fast as 4.1 seconds (BW)/6.1 seconds (Colour)  
C5535i III: As fast as 4.9 seconds (BW)/7.4 seconds (Colour)

#### Copy Resolution (dpi)

Reading: 600 x 600  
Printing: 1200 x 1200

#### Multiple Copies

Up to 999 Copies

#### Copy Exposure

Automatic or Manual (9 Levels)

#### Magnification

25%-400% (1% Increments)

#### Preset Reductions

25%, 50%, 64%, 73%, 78%

#### Preset Enlargements

121%, 129%, 200%, 400%

#### Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper Setting, Previous Settings, Favorite Settings, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Setting Confirmation/Cancel

#### Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Density Adjustment, Original Type Selection, Transparency Cover Sheets, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Job Done Notice, Mirror Image, Print on Tab, Store in Mail Box, Superimpose Image, Copy ID Card, Skip Blank Pages, Detect Feeder Multi Sheet Feed, Free Size Original, Colour Balance, Adjust One-Touch Colour, Area Designation

## Scan Specifications

#### Type

Colour Platen and Single-pass Duplexing Automatic Document Feeder

#### Document Feeder Paper Capacity

150 Sheets (20 lb. Bond)

#### Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Custom Size: 5" x 5-1/2" to 12" x 17"

#### Document Feeder Supported Media Weights

BW Original: 13 lb. Bond to 58 lb. Cover (50 to 157 g/m<sup>2</sup>)  
Colour Original: 17 lb. Bond to 58 lb. Cover (64 to 157 g/m<sup>2</sup>)

#### Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height: up to 2" (50 mm), Weight: Up to 4.4 lb. (2kg)]

#### Full Scan

Colour Network ScanGear2 for both Twain and WIA  
Supported OS: Windows 7/8.1/10  
Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016

#### Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

#### Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

#### Scan Speed (Letter)

Single-sided Scanning (BW): 80 ipm (300 dpi)/80 ipm (600 dpi)  
Single-sided Scanning (Colour): 80 ipm (300 dpi)/60 ipm (600 dpi)  
Double-sided Scanning (BW): 160 ipm (300 dpi)/150 ipm (600 dpi)  
Double-sided Scanning (Colour): 160 ipm (300 dpi)/80 ipm (600 dpi)

## Send Specifications

#### Destination

Email/Internet Fax (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)

#### Colour Mode

Automatic-Colour Select (Full Colour/Greyscale), Automatic-Colour Select (Full Colour/Black-and-White), Full colour, Greyscale, and Black-and-White

#### Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

#### Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

#### Communication Protocol

File: FTP (TCP/IP), SMB v3.0, WebDAV  
Email: SMTP, POP3

#### File Format

Standard: TIFF, JPEG, PDF (Encrypted, Compact, Searchable, Apply Policy, Optimize for Web, PDF A/1-b), Limited Colour, Device Signature, XPS (Compact, Searchable, Device Signature), Office Open XML (PowerPoint<sup>®</sup>, Word)  
Optional: PDF (Trace & Smooth, User Signature), XPS (User Signature)

#### Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Detect Feeder Multi Sheet Feed

## Fax Specifications

#### Maximum Number of Connection Lines

4

#### Modem Speed

Super G3: 33.6 kbps  
G3: 14.4 kbps

#### Compression Method

MH, MR, MMR, JBIG

#### Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

#### Sending/Recording Size

Statement-R to 11" x 17"

#### Fax Memory

Up to 30,000 Pages

#### Speed Dials

Max. 200

#### Group Dials/Destinations

Max. 199 Dials

#### Sequential Broadcast

Max. 256 Addresses

#### Memory Backup

Yes

#### Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Select Line, Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed

## Store Specifications

### Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

### Advanced Box

Communication Protocol: SMB or WebDAV Supported

Client PC: Windows (Windows 7/8.1/10)

Concurrent Connections (Max.)

SMB: 64

WebDAV: 3 (Active Sessions)

### Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD)

Approx. 480 GB (With Optional 1 TB HDD)

### Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password

### Memory Media

Standard: USB

## Security Specifications

### Authentication

Standard: Universal Login Manager, uniFLOW Online Express,<sup>12</sup> User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in  
Optional: uniFLOW

### Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup, McAfee Embedded Control<sup>21</sup>  
Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

### Network

Standard: Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

### Document

Standard: Secure Watermark, Encrypted PDF, Encrypted Secure Print, Digital Signatures, Adobe LiveCycle® Rights Management ES2.5 Integration  
Optional: User Signatures, Document Scan Lock

## Environmental Specifications

### Operating Environment

Temperature: 50 to 86 °F

Humidity: 20 to 80 % RH (Relative Humidity)

### Power Requirements

C5560i III/  
C5550i III: 120-127V AC 60 Hz, 11.5 A

C5540i III/  
C5535i III: 120-127V AC, 60 Hz, 10 A

### Plug (Main Unit)

C5560i III/  
C5550i III: NEMA 5-20P

C5540i III/  
C5535i III: NEMA 5-15P

### Power Consumption

Maximum: Approx. 1,800 W

Standby: Approx. 65.2 W<sup>3</sup>

Sleep Mode: Approx. 0.8 W<sup>4</sup>

Typical Electricity Consumption (TEC) Rating<sup>22</sup>:

C5560i III: 0.86 kWh

C5550i III: 0.70 kWh

C5540i III: 0.58 kWh

C5535i III: 0.46 kWh

## BOOKLET FINISHER-Y1 (External)

Number of Trays:	3
Top Tray Capacity: <sup>17</sup>	Letter/Executive/Statement/Statement-R (3,000 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (1,500 Sheets)
Lower Tray Capacity: <sup>17</sup>	Letter/Executive/Statement/Statement-R (250 Sheets), 12" x 18"/11" x 17"/Legal/Letter-R (125 Sheets)

### Paper Weight

Top Tray:	14 lb. Bond to 140 lb. Index (52 to 256 g/m <sup>2</sup> )
Lower Tray:	14 lb. Bond to 110 lb. Cover (52 to 300 g/m <sup>2</sup> )

Staple Position: Corner, Double

### Staple Capacity

Corner Staple and Double Staple Letter/Executive:	50 Sheets [24 lb. Bond (90 g/m <sup>2</sup> )]
11" x 17"/Legal/30 Sheets [24 lb. Bond (90 g/m <sup>2</sup> )]	

Letter-R:

Staple-Free Staple

11"x17"/Letter:	5 Sheets [14 to 17 lb. Bond (52 to 64 g/m <sup>2</sup> )]
	4 Sheets [17.3 to 21.7 lb. Bond (65 to 81.4 g/m <sup>2</sup> )]
	3 Sheets [21.7 to 28 lb. Bond (81.5 to 105 g/m <sup>2</sup> )]

Staple On Demand:

Booklet-Stitch Paper Size:	12" x 18", 11" x 17", Legal, Letter-R, Custom Size [7-3/4" x 10-5/8" to 12" x 18" (195 mm x 270 mm to 304.8 mm x 457.2 mm)]
Booklet-Stitch Staple Capacity:	20 Sheets x 10 Sets [22 lb. Bond (81 g/m <sup>2</sup> )] (including one cover sheet up to 140 lb.) Index (256 g/m <sup>2</sup> )

Power Source: From the Main Unit/85.6 W

Dimensions (W x D x H):	25-1/8" x 24-1/2" x 45" (637 mm x 623 mm x 1142 mm)
Weight:	Approx. 125.7 lb (57 kg)

## INNER 2/3-HOLE PUNCHER-B1

(Requires the INNER FINISHER-H1)

Acceptable

Punch Paper Weight:	14 lb. Bond to 110 lb. Cover (52 to 300 g/m <sup>2</sup> )
---------------------	------------------------------------------------------------

Acceptable Punch Paper Size

Two Holes:	11" x 17", Legal, Letter, Letter-R, Executive
Three Holes:	11" x 17", Letter, Executive

Power Source: From the Main Unit

## 2/3-HOLE PUNCHER-A1

(Requires either the STAPLE FINISHER-Y1 or BOOKLET FINISHER-Y1)

Acceptable

Punch Paper Weight:	14 lb. Bond to 110 lb. Cover (52 to 300 g/m <sup>2</sup> )
---------------------	------------------------------------------------------------

Acceptable Punch Paper Size

Two holes:	11" x 17", Legal, Letter, Letter-R, Executive
Three holes:	11" x 17", Letter, Executive
Power Source:	From the Main Unit

## Hardware Options

### Card Readers

MICARD PLUS PROXIMITY CARD READER
COPY CARD READER-F1
COPY CARD READER ATTACHMENT-B5

### Others

CABINET TYPE-N
BUFFER PASS UNIT-L1
COPY TRAY-J2
UTILITY TRAY-B1
PLATEN COVER TYPE W
PRINTER COVER-J1
TAB FEEDING ATTACHMENT-F1
USB KEYBOARD

## Security Options

### Document Security

DOCUMENT SCAN LOCK KIT-B2
iR-ADV SECURITY KIT-P1 FOR IEEE 2600.1 COMMON CRITERIA CERTIFICATION <sup>17</sup>

### Data Security

HDD MIRRORING KIT-J1
2.5"/250 GB HDD-N1
2.5"/1 TB HDD-P1
REMOVABLE HDD KIT-A1

## System and Controller Options

### Print Accessories

PCL INTERNATIONAL FONT SET-A1
-------------------------------

### Barcode Printing

BARCODE PRINTING KIT-D1
-------------------------

### EFI-Fiery Based Controller

imagePASS-P2
REMOVABLE HARD DISK DRIVE KIT-B1
FIERY IMPOSE
FIERY COMPOSE
FIERY IMPOSE AND COMPOSE

### System Accessories

COPY CONTROL INTERFACE KIT-A1
CONNECTION KIT-A1 FOR BLUETOOTH LE
NFC KIT-C1
MEAP WEB CONNECTION KIT-V5.3 <sup>18</sup>

### Fax Accessories

SUPER G3 FAX BOARD-AS2
------------------------

SUPER G3 2ND LINE FAX BOARD-AS2
SUPER G3 3RD/4TH LINE FAX BOARD-AS2
REMOTE FAX KIT-A1
IP FAX EXPANSION KIT-B1

## Other Options

### Accessibility Accessories

ADF ACCESS HANDLE-A1
VOICE GUIDANCE KIT-G1
VOICE OPERATION KIT-D1
BRaille LABEL KIT-F1

### Staples

STAPLE-P1 <sup>19</sup>
STAPLE CARTRIDGE-Y1 <sup>20</sup>

<sup>1</sup> Some types of tracing paper cannot be used.

<sup>2</sup> Time from device power-on to when copy jobs can be programmed with Quick Start Up mode.

<sup>3</sup> Time from exiting Sleep mode to when printing is operational.

<sup>4</sup> Time from device power-on to when key operation can be performed on the touch screen.

<sup>5</sup> Includes main unit and either Cassette Feeding Unit-AM1, High Capacity Cassette Feeding Unit-A1, or Cabinet Type-N.

<sup>6</sup> Includes main unit, consumables, and Cassette Feeding Unit-AM1.

<sup>7</sup> PDF print from Web sites is supported.

<sup>8</sup> EPS can be printed directly only from the Remote User Interface.

<sup>9</sup> Requires the optional PCL International Font Set-A1.

<sup>10</sup> Requires the optional Barcode Printer Kit-D1.

<sup>11</sup> Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

<sup>12</sup> No charge for this solution; however activation is required.

<sup>13</sup> Reference value (measured one unit).

<sup>14</sup> 0.8 W sleep mode not available in all circumstances due to certain settings.

<sup>15</sup> GPR-55L Toner also available for Colour (C, M, Y). Yield (estimated @ 5% coverage) is 26,000 images.

<sup>16</sup> With 20 lb. Bond (80 gsm) paper.

<sup>17</sup> Will launch at a later date.

<sup>18</sup> No charge for this option; however it does need to be ordered.

<sup>19</sup> Used for corner/double stapling only. 2 cartridges per case. 5,000 staples per cartridge.

<sup>20</sup> Used for booklet finishing only. 3 cartridges per case. 2,000 staples per cartridge.

<sup>21</sup> Requires Unified Firmware Platform v3.9

<sup>22</sup> Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0.

WWW.CANON.CA



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR guidelines for energy efficiency. The ENERGY STAR mark is a registered mark in Canada. McAfee and the McAfee logo are trademarks of McAfee LLC in Canada and/or other countries. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks of Canon Inc. in Canada and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. "II" indicates that this model has been upgraded to new system software and includes additional security features as standard. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon Canada Inc. does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with a Canon Sales Representative or a Canon Authorized Dealer for details. All printer output images are simulated. Products are shown with optional accessories. Specifications and availability subject to change without notice. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory or statutory compliance. Not responsible for typographical errors.

©2019 Canon Canada Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.



McAfee  
PROTECTED

UFP UNIFIED  
FIRMWARE  
PLATFORM

CANON  
GENUINE  
TONER, CARTRIDGE  
& PARTS



Canon

To learn about Canon's many awards,  
visit [www.canon.ca/awards](http://www.canon.ca/awards)